



CA-FC5-SH-MIC4 Product Description

This shielded cable has 26 AWG conductors, a 5-position latching connector (Molex 14-60-0052 (https://www.molex.com/molex/products/part-detail/rb_cbl_wr_trp_conn/0014600052)) on one end and a 4-pin Molex micro-connector (consisting of a housing (51021-0400) (https://www.molex.com/en-us/products/partdetail/510210400), and 4 crimp terminals (50079-8001) (https://www.molex.com/en-us/products/part-detail/500798001)) on the other end. This cable is used with several different products in our offerings, such as connecting US Digital's E4T (https://www.usdigital.com/products/encoders/incremental/kit/e4t/) or E8T miniature optical kit encoder (https://www.usdigital.com/products/encoders/incremental/kit/e8t/) to an interface product that accepts a 5-pin latching connector.


WARNING: This product can cause exposure to substances, such as phthalate plasticizers, known to the State of California to cause cancer and reproductive harm. For more information, go to oehha.ca.gov/proposition-65 (https://oehha.ca.gov/proposition-65).

Specifications





PIN-OUT




4-PIN SIDE			5-PIN SIDE		
Pin	Description	Color	Pin	Description	Color
1	+5VDC power	Red	1	Ground	Black
2	A Channel	Green	2	-	-
3	Ground	Black	3	A Channel	Green
4	B Channel	Yellow	4	+5VDC power	Red
			5	B Channel	Yellow

Notes

• US Digital® warrants its products against defects in materials and workmanship for two years. See complete warranty (https://www.usdigital.com/company/warranty) for details.

Configuration Options



PLEASE NOTE: This chart is for informational use only. Certain product configuration combinations are not available. Visit the CA-FC5-SH-MIC4 product page (https://www.usdigital.com/products/CA-FC5-SH-MIC4) for pricing and additional information.



